# ROTADAIRON® SMA 305

# PNEUMATIC SEEDER FOR TRACTOR

WEEDING

RAKING

SOIL PREPARATION

SEEDING

OVERSEEDING

DETHATCHING-

MULCHING





# PNEUMATIC SEEDER FOR TRACTOR

# **SMA** 305

### Functions of the seeder SMA 305

This seeder has been designed to seed most varieties of turf such as pastures, fescues, ryegrass, etc. on large surfaces. It is equipped with a pneumatic seeder and two cast iron rollers, allowing seeding in one pass. It is used on land previously worked with a soil preparation/stone burier.

## Quality of service





A large stock of spare parts is permanently maintained at our factory. Our partners have online tools and quick access to manufacturer information. Maintain the quality and performance of your Rotadairon® by using only original parts.


1 Swing	rear	roller
---------	------	--------

- 2 Locking of the oscillation of the rear roller for road travel
- 3 Drive wheel allowing the deposit of the seed in proportion to the advance
- 4 Access platform for the tank
- 5 Front and rear roller scraper
- Pneumatic seeder

Machine	SMA 305	
Seeding width	3310 mm (130''1/4)	
Total width	3600 mm (141" 3/4)	
Weight	1640 Kg (3615.5 lb)	
Tractor : Required power	60 - 100 CV	
Front roller type	Cast iron serrated disc roller	
Front roller diameter	Ø 400 mm (15" 3/4)	
Rear roller type	Cast iron serrated disc roller	
Rear roller diameter	Ø 295 mm (11" <sub>1/2</sub> )	
3 point hitch	Categorie 2	
Tractor forward speed	3 to 8 Km/h (1.8 to 5 mph)	
Transport dimension w x L x H	3600 mm x 2420 mm x 2340 mm (141" 3/4 x 95" 1/4 x 92")	
Seeder		
Type of seed drill	Pneumatic seed drill	
Seed rate adjustement	Dosing ruler	
Seed drill capacity	750 liters (198 US gal)	
Option	Available in double rear cast iron rollers	









**ROTADAIRON** Départementale 92 - Les Hunaudières 72230 Mulsanne - France Mail: contacts@rotadairon.fr Phone number: (33) 2 43 422 422

